



Increase IOPs without sacrificing data integrity.

Kingston's SSDNow E50 features high IOPs and bandwidth performance to solve I/O latencies and bottlenecks and increase your server's performance. E50's 6Gbps SATA interface provides max bandwidth over 500MB/s read/write. This drive is built with MLC Sync NAND and is rated at 60,000 read/write IOPS versus an average IOPS rating of 300 for a 15K SAS HDD.

E50's advanced data integrity protection gives you peace of mind by ensuring a longer life for your data and your drive. DuraWrite™ extends the life of the SSD by efficiently reducing the Flash writes without sacrificing data integrity. RAISE™ technology provides superior protection against uncorrectable errors, while overprovisioning and advanced wear-leveling ensure consistent performance and wear over the life of the drive.

SSDNow E50 also features intelligent power failure protection to prevent data loss in case of a power failure. It's backed by a three-year warranty, free technical support and legendary Kingston® reliability.

- > High IOPS and bandwidth performance
- > Advanced data integrity protection
- > Intelligent power failure protection

SSDNow E50



SSDNow E50 is ideal for:

- Server boot time improvements
- Server pagefile storage
- Server caching
- Server application & storage acceleration

Features/specs on reverse >>

SOLID STATE DRIVE
 FLASH STORE
 DURABLE MEMORY
 FLASH STORE
 PC PERFORMANCE
 FLASH SUPGRADE KIT
 STORE

SSDNow E50

FEATURES/BENEFITS

- > **Performance** — higher IOPS for multi-user environments
- > **Endurance** — Data Integrity Protection featuring DuraClass technology
- > **Dependable** — RAISE for advanced data reliability
- > **Durable** — DuraWrite optimizes writes to extend endurance
- > **Warranty/support** — three-year warranty with free technical support

SPECIFICATIONS

- > **Form factor** 2.5"
- > **Interface** SATA Rev. 3.0 (6Gb/s) – with backwards compatibility to SATA Rev. 2.0 (3Gb/s)
- > **Capacities**¹ 100GB, 240GB, 480GB
- > **Controller** SandForce-SF2581
- > **Encryption** AES 128bit
- > **Sequential Read/Write**² SATA Rev. 3.0 – 100GB – up to 550/530MB/s
 240GB – up to 550/530MB/s
 480GB – up to 530/500MB/s
- > **Maximum 4k Read/Write**² 100GB — 85,000/ 80,000 IOPS
 240GB — 85,000/ 73,000 IOPS
 480GB — 74,000/ 36,000 IOPS
- > **Random 4k Read/Write**² 100GB — 27,000/ 82,000 IOPS
 240GB — 48,000/ 72,000 IOPS
 480GB — 53,000/ 32,000 IOPS
- > **Additional Features** Enterprise SMART Tools
- > **Total Bytes Written (TBW)**³ 100GB – 310TB 3 DWPD⁴
 240GB – 739TB 3 DWPD⁴
 480GB – 1747TB 3 DWPD⁴
- > **Power Consumption**
 1.25 W Idle / 1.27 W Avg / 1.43 W (MAX) Read / 2.74 W (MAX) Write
- > **Storage temperatures** -40°C ~ 85°C
- > **Operating temperatures** 0°C ~ 70°C
- > **Dimensions** 69.9mm x 100mm x 7mm
- > **Weight** 92.34g
- > **Vibration operating** 2.17G Peak (7–800Hz)
- > **Vibration non-operating** 20G Peak (10–2000Hz)
- > **MTBF** 1 million hours
- > **Warranty/support** three-year warranty with free technical support



KINGSTON PART NUMBERS

SE50S37/100G
 SE50S37/240G
 SE50S37/480G



¹ Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's Flash memory Guide at kingston.com/flashguide.

² Based on "out-of-box performance." Speed may vary due to host hardware, software and usage.

³ Total Bytes Written (TBW) is derived from the JEDEC Workload (JESD219A).

⁴ Drives Writes Per Day (DWPD)

THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE

©2013 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-266US

